



## NOIV.E27764 Auxiliary Devices for Use in Hazardous Locations

### Auxiliary Devices for Use in Hazardous Locations

[See General Information for Auxiliary Devices for Use in Hazardous Locations](#)

**VENTURE MEASUREMENT L L C**  
150 VENTURE BLVD  
SPARTANBURG, SC 29306 USA

E27764

#### **Class I, Groups C and D; Class II, Groups E, F and G.**

Machine-operated switches:

"Auto-Bin-Dicator" Models ABX-R, -S, EP-SS-1, -SS-2.

"Flo-Guard PD-1 followed by A, followed by O, followed by L03, L06, L12 or LXX, followed by D or G, followed by 1, 2, followed by A.

"Flo-Guard PD-2 followed by A, followed by O, followed by L03, L06, L12 or LXX, followed by D or G.

Level indicators, Series RF-8, -9, -10, -11, -12, -17, -18, -82, with the following Models: Level indicator with cable probe, Model RF-8 followed by L, followed by 0, 2, 4 or 5, followed by X, followed by 1, 2, 3, 4 or 7, followed by A, N or S, followed by 0 or other numbers; Model RF-82 followed by L, followed by 0, 2, 4 or 5, followed by X, followed by 1, 2, 3, 4 or 7, followed by A, N or S, followed by 0 or other numbers, followed by N, O, S or T. Level indicator with integral probe, Model RF-8 followed by A, H, I or O, followed by 0, 1, 2, 4, 5, 6, 7, 8, A, J, T or U, followed by X, followed by 1, 2, 3, 4 or 7, followed by A, B, C, H, N or S; Model RF-9 followed by C, D, M or N, followed by 0, 1, 2, 4, 5, 6, 7, 8, A, J, T or U, followed by X, followed by 1, 2, 3, 4, 5, 6 or 7, followed by A, B, C, H or S; Model RF-9 followed by 1 or 2, followed by C, D, M or N, followed by 0, 1, 2, 4, 5, 6, 7, 8, A, J, T or U followed by X, followed by 1, 2, 3, 4, 5, 6 or 7, followed by A, B, C, H, or S; Model RF-82 followed by C or D, followed by 0, 1, 2, 4, 5, 6, 8, A, J, T or U followed by X, followed by 1, 2, 3, 4, 5, 6 or 7, followed by A, H, N or S. Level indicators with remote probe, Model RF-10E followed by C, D, M or N, followed by 1 or 2, followed by X, followed by 1, 2, 3, 4, 5, 6 or 7; Model RF-1, followed by 1 or 2, followed by E, followed by C, D, G, M or N, followed by 1 or 2, followed by X, followed by 1, 2, 3, 4, 5, 6 or 7. Remote probe assemblies, Model RF-10P followed by A, B, C, D or S, followed by 0, 1, 2, 4, 5, 6, 7, 8, A or J, followed by X, followed by 1.

Model RF-17 followed by E, followed by O or G, followed by 1, followed by X, followed by 1, 2, 3, 4, 5, 6 or 7. Model RF-18 followed by E, followed by C or K, followed by 1, followed by X, followed by 1, 2, 3, 4, 5, 6 or 7.

Level indicators: "Roto-Bin-Dicator" Models RSS1X-1, -2X-1, -3X-1, RX-H, RXA-H, RXB-H, RXC-H, RXAF-H, RXCF-H.

"Super Safe Roto" Models RSSP1X, -2X.

[Last Updated](#) on 1999-11-18

[Copyright © 2008 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2008 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

